

# 02

casterdepot.com


## Institutional Casters

CAPACITY TO 350



Easy rolling, double ball bearing casters are ideally suited for virtually any operation where a smooth, highly maneuverable caster is required. Heat treated design delivers extended life and performance.

### MOUNTING OPTIONS



### TYPICAL APPLICATIONS

- Hotel equipment
- Institutional equipment
- Food service racks and cases
- Stock carts
- Laundry trucks



**Expandable Adapter**  
Kit numbers on next page. To order on caster consult factory.



**Threaded Stem**  
1/2" diameter  
13NC x 1", 1-1/2"  
or 2-1/2" long  
(see next page)

## Plate Models

+ For swivel models add "S", for rigid model add "R" to end of base caster number.

Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
-------------------------	----------------------	---	-------------------------	----------------------	-------------------	---------------------

### Soft Rubber (01 Straight Roller Bearing)\*

RR	3	1 1/4	125	4 1/4	1 5/16	1.75	02RR03001
	3 1/2	1 1/4	150	4 11/16	1 1/4	1.75	02RR03X01
	4	1 1/4	150	5 1/8	1 1/4	2.25	02RR04001
	5	1 1/4	175	6 3/16	1 1/2	2.75	02RR05001

\*Plain bore (41) available. Change "01" to "41" (Example: 02RR03041).

### Hard Rubber (41 Plain Bore)


RN	3	1 1/4	300	4 1/4	1 5/16	2.00	02RN03041
	3 1/2	1 1/4	350	4 11/16	1 1/4	2.00 <td>02RN03X41</td>	02RN03X41
	4	1 1/4	350	5 1/8	1 1/4	2.25 <td>02RN04041</td>	02RN04041
	5	1 1/4	350	6 3/16	1 1/2	2.75 <td>02RN05041</td>	02RN05041
	6	1 1/4	350	7 1/4	1 1/2	3.25 <td>02RN06041</td>	02RN06041



### FEATURES

- **Top Plate & Yoke:** Heavily embossed, formed steel to extend caster life under rugged conditions
- **Swivel Section:** Heat treated double ball bearing raceways to resist wear and improve maneuverability
- **Kingpin:** 1/2" hydraulically formed steel rivet
- **Axle:** 3/8" diameter hollow axle with lock nut
- **Finish:** All rigs are zinc plated to resist rust and corrosion
- **NSF** Listed for food service industry, consult factory
- Alternate or custom caster configurations available

### BEARING OPTIONS



### RIG OPTIONS

- **Sealed wheel** (1/2" straight roller bearing with 1-1/16" bore) specify **SW02**
- **Sealed swivel** specify **SS01**
- Special **zerk fitting** for axle specify **ZF03**
- **"NSF"** listed for food industry, consult factory
- **Hollow kingpin** swivel rig available specify **YH** in place of wheel code (02YH03001S)
- **Stainless steel** versions available, see page 77

### BRAKE OPTIONS

To order, add brake code below to end of model. Example: 02XS05031SGL

**Grip Lock**  
specify **GL**



**Face Contact**  
specify **F**

**Total Lock**  
specify **T**



+ For swivel models add "S", for rigid model add "R" to end of base caster number.

Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
-------------------------	----------------------	---	-------------------------	----------------------	-------------------	---------------------

### X-tra Soft Rubber Flat Tread (31 Annular Ball)\*

XS	3	1 1/4	200	4 1/4	1 5/16	1.75	02XS03031
	3 1/2	1 1/4	250	4 11/16	1 1/4	1.85 <td>02XS03X31</td>	02XS03X31
	4	1 1/4	300	5 1/8	1 1/4	2.00 <td>02XS04031</td>	02XS04031
	5	1 1/4	325	6 3/16	1 1/2	2.25 <td>02XS05031</td>	02XS05031
	6	1 1/4	350	7 1/4	1 1/2	2.40 <td>02XS06031</td>	02XS06031

\*Delrin (51) bearing available. Change "31" to "51" (Example: 02XS03051).

### Precision X-tra Soft Round Tread (28 Precision Ball Bearing)

XR	3	1 1/4	200	4 1/4	1 5/16	1.75	02XR03028
	3 1/2	1 1/4	250	4 11/16	1 1/4	1.85 <td>02XR03X28</td>	02XR03X28
	4	1 1/4	300	5 1/8	1 1/4	2.00 <td>02XR04028</td>	02XR04028
	5	1 1/4	325	6 3/16	1 1/2	2.25 <td>02XR05028</td>	02XR05028

### Polypropylene (41 Plain Bore)\*

PB	3	1 1/4	250	4 1/4	1 5/16	1.75	02PB03041
	4	1 1/4	350	5 1/8	1 1/4	2.00 <td>02PB04041</td>	02PB04041
	5	1 1/4	350	6 3/16	1 1/2	2.25 <td>02PB05041</td>	02PB05041

\*Delrin (51) bearing available. Change "41" to "51" (Example: 02PB03051).

### Polyurethane on Polypropylene (28 Precision Ball Bearing)\*

XA	3	1 1/4	300	4 1/4	1 5/16	1.50	02XA03028
	3 1/2	1 1/4	350	4 11/16	1 1/4	1.50 <td>02XA03X28</td>	02XA03X28
	4	1 1/4	350	5 1/8	1 1/4	2.25 <td>02XA04028</td>	02XA04028
	5	1 1/4	350	6 3/16	1 1/2	2.75 <td>02XA05028</td>	02XA05028


\*Annular (31) and Delrin (51) bearing available. Change "28" to "31" or "51" (Example: 02XA030331).

Continue on next page >>


## Plate Models

Continued from previous page

+ For swivel models add "S", for rigid model add "R" to end of base caster number.


	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
<b>Phenolic (01 Straight Roller Bearing)*</b>							
<b>TM</b> 	3	1 1/4	350	4 1/4	1 5/16	1.50	<b>02TM03001</b>
	3 1/2	1 1/4	350	4 11/16	1 1/4	2.00	<b>02TM03X01</b>
	4	1 1/4	350	5 1/8	1 1/4	2.00	<b>02TM04001</b>
	5	1 1/4	350	6 3/16	1 1/2	2.75	<b>02TM05001</b>
	*Plain bore (41) bearing available. Change "01" to other bearing code (Example 02TM03041).						


+ For swivel models add "S", for rigid model add "R" to end of base caster number.


	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
<b>Cast Iron (01 Straight Roller Bearing)*</b>							
<b>CA</b> 	3	1 1/4	200	4 1/4	1 5/16	2.50	<b>02CA03001</b>
	3 1/2	1 1/4	250	4 11/16	1 1/4	2.50	<b>02CA03X01</b>
	4	1 1/4	300	5 1/8	1 1/4	3.00	<b>02CA04001</b>
	5	1 1/4	325	6 3/16	1 1/2	3.50	<b>02CA05001</b>
	*Plain bore (41) available. Change "01" to other bearing code (Example 02CA03041).						


## Threaded Stem Models


Base caster numbers shown in chart. To order see stem codes below.


	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number
<b>Soft Rubber (01 Straight Roller Bearing)*</b>							
<b>RR</b> 	3	1 1/4	125	4 3/32	1 5/16	1.75	<b>02RR03001</b>
	3 1/2	1 1/4	150	4 17/32	1 1/4	1.75	<b>02RR03X01</b>
	4	1 1/4	150	4 31/32	1 1/4	2.25	<b>02RR04001</b>
	5	1 1/4	175	6 1/32	1 1/2	2.75	<b>02RR05001</b>


	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number
<b>Polypropylene (41 Plain Bore)*</b>							
<b>PB</b> 	3	1 1/4	250	4 3/32	1 5/16	1.75	<b>02PB03041</b>
	4	1 1/4	350	4 31/32	1 1/4	2.00	<b>02PB04041</b>
	5	1 1/4	350	6 1/32	1 1/2	2.25	<b>02PB05041</b>
	*Delrin (51) bearing available. Change "41" to "51" (Example: 02PB03051).						


	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number
<b>Hard Rubber (41 Plain Bore)</b>							
<b>RN</b> 	3	1 1/4	300	4 3/32	1 5/16	2.00	<b>02RN03041</b>
	3 1/2	1 1/4	350	4 17/32	1 1/4	2.00	<b>02RN03X41</b>
	4	1 1/4	350	4 31/32	1 1/4	2.25	<b>02RN04041</b>
	5	1 1/4	350	6 1/32	1 1/2	2.75	<b>02RN05041</b>
	6	1 1/4	350	7 3/32	1 1/2	-	<b>02RN06041</b>

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number
<b>Polyurethane on Polypropylene (31 Annular Ball)*</b>							
<b>XA</b> 	3	1 1/4	300	4 3/32	1 5/16	1.50	<b>02XA03031</b>
	3 1/2	1 1/4	350	4 17/32	1 1/4	1.50	<b>02XA03X31</b>
	4	1 1/4	350	4 31/32	1 1/4	2.25	<b>02XA04031</b>
	5	1 1/4	350	6 1/32	1 1/2	2.75	<b>02XA05031</b>
	*Delrin (51) bearing available. Change "31" to "51" (Example: 02XA03051).						

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number
<b>X-tra Soft Rubber Flat Tread (31 Annular Ball)*</b>							
<b>XS</b> 	3	1 1/4	200	4 3/32	1 5/16	1.75	<b>02XS03031</b>
	3 1/2	1 1/4	250	4 17/32	1 1/4	1.85	<b>02XS03X31</b>
	4	1 1/4	300	4 31/32	1 1/4	2.00	<b>02XS04031</b>
	5	1 1/4	325	6 1/32	1 1/2	2.25	<b>02XS05031</b>
	6	1 1/4	350	7 3/32	1 1/2	-	<b>02XS06031</b>
	*Delrin (51) bearing available. Change "31" to "51" (Example: 02XS03051).						

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number
<b>Phenolic (01 Straight Roller Bearing)*</b>							
<b>TM</b> 	3	1 1/4	350	4 3/32	1 5/16	1.50	<b>02TM03001</b>
	3 1/2	1 1/4	350	4 17/32	1 1/4	2.00	<b>02TM03X01</b>
	4	1 1/4	350	4 31/32	1 1/4	2.00	<b>02TM04001</b>
	5	1 1/4	350	6 1/32	1 1/2	2.75	<b>02TM05001</b>
	Plain bore (41) available. Change "01" to bearing code. (Example: 02TM03041).						

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number
<b>Precision X-tra Soft Round Tread (28 Precision Ball Bearing)*</b>							
<b>XR</b> 	3	1 1/4	200	4 3/32	1 5/16	1.75	<b>02XR03028</b>
	3 1/2	1 1/4	250	4 17/32	1 1/4	1.85	<b>02XR03X28</b>
	4	1 1/4	300	4 31/32	1 1/4	2.00	<b>02XR04028</b>
	5	1 1/4	325	6 1/32	1 1/2	2.25	<b>02XR05028</b>

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number
<b>Cast Iron (01 Straight Roller Bearing)*</b>							
<b>CA</b> 	3	1 1/4	200	4 3/32	1 5/16	2.50	<b>02CA03001</b>
	3 1/2	1 1/4	250	4 17/32	1 1/4	2.50	<b>02CA03X01</b>
	4	1 1/4	300	4 31/32	1 1/4	3.00	<b>02CA04001</b>
	5	1 1/4	325	6 1/32	1 1/2	3.50	<b>02CA05001</b>
	*Plain bore (41) available. Change "01" to other bearing code. (Example: 02CA03041).						

**Threaded Stem Order Codes (To order, add to base number above. Example: 02RR03001S32) Note: Threads are 1/2" Diameter 13 NC**

Wheel Diameter (Inches)	Type 1: 1" Long Option Code	Type 2: 1-1/2" Long Option Code	Type 3: 2-1/2" Long For Expandable Adapters Option Code
3	<b>S32</b>	<b>S31</b>	<b>S33</b>
3 1/2	<b>SX2</b>	<b>SX1</b>	<b>SX3</b>
4	<b>S42</b>	<b>S41</b>	<b>S43</b>
5	<b>S52</b>	<b>S51</b>	<b>S53</b>

### Hollow Kingpin Swivel Rig



Hollow kingpin swivel rig available specify **YH** in place of wheel code (02YH03001S). Hole accommodates 1/2" fittings.

To order complete caster assembly, consult factory.

### Expandable Adapter Kits

(Fits any 13 NC threaded stem caster over 2-1/2" long)



#### Stem Description For

#### Round and Square Tubing

3/4" to 7/8" (19.1mm to 22.2mm)	SX123200
7/8" to 1" (22.2mm to 25.4mm)	SX143200
1" to 1-1/8" (25.4mm to 28.6mm)	SX163200
1-1/8" to 1-1/4" (28.6mm to 31.8mm)	SX183200
1-1/4" to 1-1/2" (31.8mm to 38.1mm)	SX203200
1-1/2" to 1-3/4" (38.1mm to 44.5mm)	SX243200
1-3/4" to 2" (44.5mm to 50.8mm)	SX283200

#### Kit Number

Kits come in individual plastic bags and include nut, black rubber expander and white nylon spacer. Kits fit any 1/2" 13 NC threaded stem caster over 2-1/2" long.

To order pre-installed adapters consult factory.