



7900 SERIES

450 LBS
casterdepot.com



FEATURES

KINGPIN: 9/16" Rivet diameter
BALL BEARINGS: 5/16" diameter upper race; 1/4" diameter lower race
BUSHING: Sealed Precision Ball Bearings
AXLE&NUT: 1/2" axle and lock nut

FINISH: Corrosion resistant bright zinc
HARDENED: Sealed raceway
SPECIAL: Automotive tire traction; full floor protection; quiet operation
PLY RATING: Ply rating is 4, maximum PSI is 50

EXCELLENT FOR:

- Uneven floors such as agricultural, institutional and industrial
- Quiet Cushion ride
- Shock and Vibration
- Prolonging equipment life
- Floor Protection
- Platform and Large stock trucks
- Food Service equipment
- Hotel Equipment



PNEUMATIC LUG



PNEUMATIC SAWTOOTH

OPTIONS:

SLB Side Locking Brake

FINISHES:


70?A Antique
 70?PB Polished Brass
 70?1 Brass
 70?2 Chrome
 70?4 Black

Inquiries on other finishes welcome

WHEEL		CASTER				PART NUMBER							
Diameter	Tread Width	Capacity Lbs.	Bearing Type	Swivel Radius	Overall Height	Tire Size	Tire Colour	Leg Spacing	Wheel Type	Swivel	Caster Weight (lbs)	Rigid	Caster Weight (lbs)
8"	2 1/2"	300	Precision Ball	6 1/4"	10"	2.50-4	Black	3"	Pneumatic (Lug)	S7908-A38H-PNC-PBB	6.58	R7908-A38H-PNC-PBB	5.70
10"	3 1/2"	350	Precision Ball	7 5/8"	12 1/2"	4.10/3.50-4	Black	4"	Pneumatic (Sawtooth)	S7910-A38H-PNC-PBB	7.69	R7910-A38H-PNC-PBB	7.32
12"	3 1/2"	450	Precision Ball	9"	14"	4.10/3.50-6	Black	4"	Pneumatic (Sawtooth)	S7912-A38H-PNC-PBB	11.25	R7912-A38H-PNC-PBB	10.00

* All 8", 10" and 12" Pneumatics are fitted with a 3 pc. Split Rim / Bolt through flanged hub design

PLATE DIAGRAMS



STANDARD PLATE: A38H

Plate Thickness: 1/4"

