



MEDICAL

SERIES

220LBS
casterdepot.com



FEATURES

KINGPIN: 13mm
RACEWAY: 6002 Precision bearing
AXLE&NUT: 10mm
FINISH: Nylon 6 plus envirothane

SPECIAL:

The Medical Series caster developed with a very Soft Polyurethane Tread rolls quietly with ease without marking expensive floors. The polurethane tread is securely fastened to the nylon core and comes with precision bearings. Because of the precision bearings, Medical Caster is extremely ergonomically efficient, moving expensive equipment effortlessly. The Double Locking Brake securely locks, protecting valuable cargo.

EXCELLENT FOR:

- Medical and Diagnostic Equipment
- X-Ray Equipment
- Food Service Equipment
- Pharmaceutical Equipment

OPTIONS:

DLB Double Locking Brake


SPECIAL:

Moisture Friendly
 Non-Marking
 Quiet
 Soft Polyurethane Tread

WHEEL		CASTER			PART NUMBER		Caster Weight (lbs)
Diameter	Capacity Lbs.	Bearing Type	Swivel Radius	Overall Height	Wheel Type	Swivel	
4" (100mm)	175	Precision	3" (2.95mm)	4 15/16" (125mm)	Envirothane™ Grey	MD100W-A07E-UG-PB	1.79
	175	Precision			Envirothane™ Grey	MD100W-A07E-UG-PB-DLB	1.88
	175	Precision			Envirothane™ Grey	MD100W-M10-1.5DT-UG-PB	1.44
	175	Precision			Envirothane™ Grey	MD100W-M10-1.5DT-UG-PB-DLB	1.52
	175	Precision			Envirothane™ Grey	MD100W-M12-1.75X1HN-UG-PB	1.44
	175	Precision			Envirothane™ Grey	MD100W-M12-1.75X1HN-UG-PB-DLB	1.52
5" (125mm)	220	Precision	3 3/4" (3.73mm)	5 25/32" (147mm)	Envirothane™ Grey	MD125W-A07E-UG-PB	2.14
	220	Precision			Envirothane™ Grey	MD125W-A07E-UG-PB-DLB	2.25
	220	Precision			Envirothane™ Grey	MD125W-M12-1.75X1HN-UG-PB	1.79
	220	Precision			Envirothane™ Grey	MD125W-M12-1.75X1HN-UG-PB-DLB	1.89
	220	Precision			Envirothane™ Grey	MD125W-M16-2.0X1HN-UG-PB	1.88
	220	Precision			Envirothane™ Grey	MD125W-M16-2.0X1HN-UG-PB-DLB	1.99

* Caster weight based on Standard Plate

PLATE DIAGRAMS



STANDARD PLATE: A07E

Plate Thickness: 1/8"

STEMS

METRIC STEMS

***	DIAMETER	THREAD SIZE	LENGTH
M12-1.75X1HN	12mm	1.75	1
M16-2.0X1HN only available in the 5" (125mm)	16mm	2.0	1



HOLES

TAPPED HOLES

***	DIAMETER	MIN. DEPTH	PITCH
M10-1.5DT only available in the 4" (100mm)	M10	1	1.5

