KINGPINFREETM 65,000 LBS SPRING LOADED SERIES

FEATURES

KINGPIN: **RACEWAY:** Kingpinfree

Custom Raceway: Thrust bearing, Tapered bearing

and Kingpinfree

AXLE&NUT: 1 1/2" or 2" axle and lock nut, depending on wheel FINISH: Corrosion resistant bright zinc finish LUBRICATION: Grease nipple centred in head

HARDENED:

Yes LEG & SPACING: Varies depending on wheel selection and

weight capacity

SLBMF can be completely customized for a wide range of applications. Please consult our sales or engineering department. **SPECIAL:**

EXCELLENT FOR:

- Abusive conditions
- Aerospace industry
- Tow lines
- Heavy service equipment
- Aircraft engine stands
- Ground support equipment
- Industrial platform trucks
- Die & Tooling fixtures





MOLDON URETHANE-TB



PRESSON RUBBER



SOLID PNEUMATIC



PNEUMATIC



FORGED STEEL

OPTIONS:

TSB Thumb Screw Brake Universal Wheel Brake 2PSL 2 Position Swivel Lock 4PSL 4 Position Swivel Lock Spring Loaded SL

FINISHES:

Black Blue

FINISHES:

Custom top plates Custom overall height **Custom swivel radius**

