



SLHOG™

SPRING LOADED SERIES

1,500LBS
casterdepot.com

US Patent No: D516414



FEATURES

KINGPIN: 3/4" diameter nut and bolt coined
RACEWAY: 3/8" diameter upper race; 5/16" diameter lower race; hardened steel load bearings
BUSHING: Roller bearings with drilled hardened steel spanner bushing and plastic side washers
AXLE&NUT: 1/2" zerk axle and lock nut (except with PB)

FINISH: Bright chrome
LUBRICATION: Grease nipple in lower race
HARDENED: Work hardened double ball race
LEG SPACING: 2 11/16"
SPECIAL: Uniquely designed caster is casted and buffed for awesome appearance. Customized wheels and colours.

EXCELLENT FOR:

- Tool carts
- Amusement parks
- Store fixtures
- Custom applications
- Display cases



OPTIONS:

- BB Ball Bearing
- BR Bronze Bearing
- DB Delrin Bearing
- NB Nylon Roller Bearing
- PB Precision Ball Bearing
- RBC Caged Roller Bearing
- C Raceway Seal
- SSW Steel Side Washer
- SWH Heat-treated Side Washer
- TG Thread Guards
- Z Zerk in Wheel

FINISHES:


Available in black or copper
 Inquiries on other finishes welcome



WHEEL		CASTER				PART NUMBER						
Diameter	Tread Width	Capacity Lbs.	Bearing Type	Swivel Radius	Overall Height	Wheel Type	Swivel	Caster Weight (lbs)	Rigid	Caster Weight (lbs)		
6"	2"	450	Roller	5 3/16"	8 9/16"	ProTech™ Crown	SSLHG62-A47H-PRO-RB-UWB-Δ	13.76	RSLHG62-A47H-PRO-RB-Δ	10.83		
		500	Roller			Moldon Alum. Rubber	SSLHG62-A47H-MAR-RB-UWB-Δ	14.44	RSLHG62-A47H-MAR-RB-Δ	11.51		
		500	Roller			Moldon Rubber	SSLHG62-A47H-MR-RB-UWB-Δ	16.12	RSLHG62-A47H-MR-RB-Δ	13.19		
		500	Roller			ProTech™ Flat	SSLHG62-A47H-PROF-RB-UWB-Δ	13.76	RSLHG62-A47H-PROF-RB-Δ	10.83		
		700	Roller			Polyolefin	SSLHG62-A47H-POX-RB-UWB-Δ	13.12	RSLHG62-A47H-POX-RB-Δ	10.20		
		900	Roller			Moldon Poly. Urethane	SSLHG62-A47H-MPU-RB-UWB-Δ	14.22	RSLHG62-A47H-MPU-RB-Δ	10.94		
		950	Roller			Envirothane™	SSLHG62-A47H-U-RB-UWB-Δ	14.40	RSLHG62-A47H-U-RB-Δ	11.47		
		950	Precision			Envirothane™ Grey - PB	SSLHG62-A47H-UG-PB-UWB-Δ	13.85	RSLHG62-A47H-UG-PB-Δ	11.20		
		950	Roller			Envirothane™ Grey - RB	SSLHG62-A47H-UG-RB-UWB-Δ	14.40	RSLHG62-A47H-UG-RB-Δ	11.47		
		950	Precision			Envirothane™ Grey Crowned	SSLHG62-A47H-UGC-PB-UWB-Δ	13.80	RSLHG62-A47H-UGC-PB-Δ	14.63		
		1,150	Roller			ALTHANE™	SSLHG62-A47H-AIT-RB-UWB-Δ	13.87	RSLHG62-A47H-AIT-RB-Δ	11.79		
		1,200	Roller			Moldon Alum. Urethane	SSLHG62-A47H-MAU-RB-UWB-Δ	14.40	RSLHG62-A47H-MAU-RB-Δ	11.06		
		1,200	Roller			Nyroll™	SSLHG62-A47H-NYN-RB-UWB-Δ	14.03	RSLHG62-A47H-NYN-RB-Δ	11.35		
		1,200	Roller			Phenolic	SSLHG62-A47H-PH-RB-UWB-Δ	14.72	RSLHG62-A47H-PH-RB-Δ	10.55		
		1,200	Roller			RollX™	SSLHG62-A47H-RX-RB-UWB-Δ	13.47	RSLHG62-A47H-RX-RB-Δ	11.55		
		1,200	Roller			RollX™ - Maltese Cross Red	SSLHG62-A47H-RX-RB-MC1R-UWB-Δ	13.99	RSLHG62-A47H-RX-RB-MC1R-Δ	11.33		
		1,200	Roller			RollX™ - West Coast Blue	SSLHG62-A47H-RX-RB-WC1R-UWB-Δ	13.97	RSLHG62-A47H-RX-RB-WC1-Δ	11.28		
		1,200	Roller			RollX™ - All Terrain Diamond	SSLHG62-A47H-RX-RB-DP-UWB-Δ	14.19	RSLHG62-A47H-RX-RB-DP-Δ	11.50		
		1,200	Roller			Solid Steel	SSLHG62-A47H-SS-RB-UWB-Δ	17.10	RSLHG62-A47H-SS-RB-Δ	11.23		
		1,250	Roller			Moldon Urethane	SSLHG62-A47H-UR-RB-UWB-Δ	16.58	RSLHG62-A47H-UR-RB-Δ	14.17		
1,500	Roller	Ductile Iron Crowned	SSLHG62-A47H-DIC-RB-UWB-Δ	17.56	RSLHG62-A47H-DIC-RB-Δ	11.15						
1,500	Roller	Heavy Duty RollX™	SSLHG62-A47H-RXHD-RB-UWB-Δ	13.98	RSLHG62-A47H-RXHD-RB-Δ	11.20						
1,500	Precision	RollX™ - WOW - PB	SSLHG62-A47H-RXW-PB-TG-UWB-Δ	13.93	RSLHG62-A47H-RXW-PB-TG-Δ	11.47						
1,500	Roller	RollX™ - Spoked	SSLHG62-A47H-RXW-RB-SS-UWB-Δ	14.14	RSLHG62-A47H-RXW-RB-SS-Δ	11.47						
1,500	Roller	RollX™ - WOW - RB	SSLHG62-A47H-RXW-RB-TG-UWB-Δ	13.87	RSLHG62-A47H-RXW-RB-TG-Δ	13.65						

* Caster weight based on Standard Plate
 ** Swivel caster comes standard with UWB

PLATE DIAGRAMS



STANDARD PLATE: A47H Plate Thickness: 1/4"



RollX™ Maltese Cross Red RollX™ West Coast Blue RollX™ Spoked RollX™ All Terrain Diamond RollX™ WOW