Available in Stainless Steel



FEATURES

KINGPIN: **RACEWAY: BUSHING: AXLE&NUT:**

17mm 6003Z Bearing Precision bearing 5/16" axle and lock nut FINISH: Thermoplastic Nylon LEG SPACING: 1 9/16"

SPECIAL:

The Wizard Series is exclusively developed out of reinforced thermoplastic nylon material. The Wizard is extremely ergonomically efficient. This wheel is ideal for bacteria free environments. The ALTech wheel is non-marking and secured to the polyolefin core. The ALTech has a precision ball bearing in the wheel which rolls effortlessly. Nut and bolt axle have a plastic shield.

EXCELLENT FOR:

- **Bacteria-Free Environments**
- Hospitals
- Food Service Equipment

Food Processing Machinery

AlTech	7

Pharmaceutical Equipment

OPTIONS:

DLB Double Locking Brake 4 Position Swivel Lock (special order) 4PSL Bolt Hole (for threaded stems)

SPECIAL:


Moisture Friendly All Stems Available in Stainless Steel (upon request) Non-Marking

Available in Stainless Steel

WHEEL		CASTER				PART NUMBER		
Diameter	Tread Width	Capacity Lbs.	Bearing Type	Swivel Radius	Overall Height	Wheel Type	Swivel	Caster Weight (lbs)
4"	1 1/4"	230 230	Precision Precision	3 3/8"	5 5/8"	ALTech ALTech	SWZ47-A25F-TPR-PB-TG SWZ47-A25F-TPR-PB-TG-DLB	1.28 1.45
		230 230	Precision Precision	4 7/8"	5 7/16"	ALTech ALTech	SWZ47-1/2HOLE-TPR-PB-TG SWZ47-1/2HOLE-TPR-PB-TG-DLB	0.92 1.09
5"	1 1/4"	270 270	Precision Precision	4 1/4"	6 11/16"	ALTech ALTech	SWZ57-A25F-TPR-PB-TG SWZ57-A25F-TPR-PB-TG-DLB	1.50 1.70
		270 270	Precision Precision	5 3/8"	6 1/2"	ALTech ALTech	SWZ57-1/2HOLE-TPR-PB-TG SWZ57-1/2HOLE-TPR-PB-TG-DL B	1.33 1.53

* Caster weight based on Standard Plate

PLATE DIAGRAMS



STANDARD PLATE:

A25F

Plate Thickness: 3/32"