




LHF 14/16-Series

Medium Duty Spring-Loaded Top Plate Casters with Steel Spring

 440 - 1,750 lbs

 RoHS


The LHF and BHF rig series with top plate fitting are available with the following wheels:

ALEV



Tires: High-quality elastic solid rubber in smooth rolling quality 'Blickle EasyRoll', 65° shore A, non-marking gray. Vulcanized tire.
Wheel center: Die-cast aluminum.
Bearing type: Ball bearing.
For more information refer to page 67

ALST



Tread: High-quality polyurethane-elastomer Blickle Softthane®, 75° shore A, green, non-marking, non-staining. Cast tread.
Wheel center: Die-cast aluminum.
Bearing type: Ball bearing.
For more information refer to page 71

ALTH



Tread: High-quality polyurethane-elastomer Blickle Extrathane®, 92° shore A, light brown, non-marking, non-staining. Cast tread.
Wheel center: Die-cast aluminum.
Bearing type: Ball bearing.
For more information refer to page 73

Swivel casters	Rigid casters	Wheel Ø	Wheel width	Load capacity	Spring tension	Initial tension	Spring travel	Total height	Plate size	Bolt hole spacing	For mounting bolt	Offset
		[inch] [mm]	[inch] [mm]	[lbs] [kg]	[lbs] [kg]	[lbs] [kg]	[inch] [mm]	[inch] [mm]	[inch] [mm]	[inch]	[inch]	[inch]
LHF-ALEV series												
LHF-ALEV 100K-14-SG	BHF-ALEV 100K-14-SG	4	1 1/16	440	440	66	3/4	6 7/8	4 x 4 1/2	2 5/8 x 3 3/8 / 3x3	3/8	1 1/4
LHF-ALEV 125K-14-SG	BHF-ALEV 125K-14-SG	5	1 1/16	550	530	66	13/16	7 7/8	4 x 4 1/2	2 5/8 x 3 3/8 / 3x3	3/8	1 3/4
LHF-ALEV 150K-16-SG	BHF-ALEV 150K-16-SG	6	2	880	880	110	1	9 1/2	4 1/2 x 6 1/4	2 7/8 x 5 1/4 / 3 3/8 x 4 15/16	1/2	2 1/8
LHF-ALEV 200K-16-SG	BHF-ALEV 200K-16-SG	8	2	1100	880	110	1	10 7/16	4 1/2 x 6 1/4	2 7/8 x 5 1/4 / 3 3/8 x 4 15/16	1/2	2 9/16
LHF-ALTH series												
LHF-ALTH 101K-14-FA *	BHF-ALTH 101K-14-FA *	4	1 1/16	770	440	66	3/4	6 7/8	4 x 4 1/2	2 5/8 x 3 3/8 / 3x3	3/8	1 1/4
LHF-ALTH 125K-14-FA *	BHF-ALTH 125K-14-FA *	5	1 1/16	770	530	66	13/16	7 7/8	4 x 4 1/2	2 5/8 x 3 3/8 / 3x3	3/8	1 3/4
LHF-ALTH 150K-16	BHF-ALTH 150K-16	6	2	1100	1255	110	1	9 1/2	4 1/2 x 6 1/4	2 7/8 x 5 1/4 / 3 3/8 x 4 15/16	1/2	2 9/16
LHF-ALTH 200K-16	BHF-ALTH 200K-16	8	2	1750	1255	110	1	10 7/16	4 1/2 x 6 1/4	2 7/8 x 5 1/4 / 3 3/8 x 4 15/16	1/2	2 9/16
LHF-ALST series												
LHF-ALST 100K-14	BHF-ALST 100K-14	4	1 1/16	660	440	66	3/4	6 7/8	4 x 4 1/2	2 5/8 x 3 3/8 / 3x3	3/8	1 1/4
LHF-ALST 125K-14	BHF-ALST 125K-14	5	1 1/16	770	530	66	13/16	7 7/8	4 x 4 1/2	2 5/8 x 3 3/8 / 3x3	3/8	1 3/4
LHF-ALST 150K-16-CO **	BHF-ALST 150K-16-CO **	6	2 1/8	1100	1255	110	1	9 1/2	4 1/2 x 6 1/4	2 7/8 x 5 1/4 / 3 3/8 x 4 15/16	1/2	2 9/16
LHF-ALST 200K-16-CO **	BHF-ALST 200K-16-CO **	8	2 1/8	1540	1255	110	1	10 7/16	4 1/2 x 6 1/4	2 7/8 x 5 1/4 / 3 3/8 x 4 15/16	1/2	2 9/16

* With pressed steel thread guard, zinc-plated

** With extra crowned running tread

Options



	With 'Radstop' tread lock (foot-operated)	Electrically conductive version, black rubber tire	Antistatic version, non-marking gray	With alternative spring tensions	Other designs	European metric top plate fitting 100x85 / 80x60 mm	European metric top plate fitting 140x110 / 105x75-80 mm
Product code suffix	-RA	-EL	-AS				
Available for	upon request	ALEV series upon request	ALTH series upon request	upon request	upon request	refer to G15 catalog	refer to G15 catalog