



LI 12-Series

Medium Duty Heat-Resistant Industrial Top Plate Casters

220 - 330 lbs -15° F - +480° F RoHS



The LI and B rig series with top plate fitting are available with the following wheels:

POSI



Tread: Highly heat-resistant silicone rubber Bickie TempLine® Comfort, 75° shore A, black, **non-marking**. Vulcanized tire.
Wheel center: Impact and heat-resistant nylon, gray.
Bearing type: Plain bore with teflon-coated stainless steel bushing.
For more information refer to page 81

Bickie TempLine® Comfort

POHI



Wheel: High-quality, impact and heat-resistant nylon Bickie TempLine® Performance, 85° shore D, gray.
Bearing type: Plain bore with teflon-coated stainless steel bushing.
For more information refer to page 82

Bickie TempLine® Performance

Swivel casters	Rigid casters	Swivel casters with 'stop-fix' brake	Wheel Ø [inch][mm]	Wheel width [inch][mm]	Load capacity [lbs] [kg]	Bearing type	Total height [inch] [mm]	Plate size [inch]	Bolt hole spacing [inch]	For mounting bolt [inch]	Offset [inch]
LI-POSI series											
LI-POSI 100G-12-XAT	B-POSI 100G-12-XAT	LI-POSI 100G-12-FI-XAT	4 [100]	1 9/16 [40]	220 [100]	Plain bore	5 1/8 [130]	2 1/2 x 3 3/8	1 3/4 x 2 13/16 - 3 1/16	5/16	1 7/16
LI-POSI 125G-12-XAT	B-POSI 125G-12-XAT	LI-POSI 125G-12-FI-XAT	5 [125]	1 9/16 [40]	265 [120]	Plain bore	6 1/8 [155]	2 1/2 x 3 3/8	1 3/4 x 2 13/16 - 3 1/16	5/16	1 9/16
LI-POHI series											
LI-POHI 100G-12-XAT	B-POHI 100G-12-XAT	LI-POHI 100G-12-FI-XAT	4 [100]	1 1/2 [30]	330 [150]	Plain bore	5 1/8 [130]	2 1/2 x 3 3/8	1 3/4 x 2 13/16 - 3 1/16	5/16	1 7/16
LI-POHI 125G-12-XAT	B-POHI 125G-12-XAT	LI-POHI 125G-12-FI-XAT	5 [125]	1 9/16 [40]	330 [150]	Plain bore	6 1/8 [155]	2 1/2 x 3 3/8	1 3/4 x 2 13/16 - 3 1/16	5/16	1 9/16

Image of teflon-coated stainless steel bushing (XAT)



CasterDepot

Options



	With non-marking gray rubber tire *	With ball bearings lubricated with special heat-resistant grease	With silicone rubber tread and aluminum wheel center	LI-POHI series wheel Ø 3 1/8", 6", 8"	With bolt hole, for mounting bolt Ø 1/2"	Heat-resistant heavy duty casters up to 2,750 lbs	European metric top plate fitting 100x85 / 80x60 mm
Product code suffix	-SG	-HK	LI-ALSI series		LIR series		
Available for	POSI series upon request	POHI series upon request	wheel Ø 4" upon request	upon request	wheel Ø 3 1/8" - 5" upon request	upon request	refer to G15 catalog

* Operating temperature up to +465° F