


LIX Series

Medium Duty Heat-Resistant Stainless Steel Industrial Top Plate Casters - Metric Standards

220 - 330 lbs -15° F - +480° F ✓RoHS



The LIX and BX rig series with top plate fitting are available with the following wheels:

POSI		Tread: Highly heat-resistant silicone rubber Bickie TempLine® Comfort, 75° shore A, black, non-marking . Vulcanized tire. Wheel center: Impact and heat-resistant nylon, gray. Bearing type: Plain bore with teflon-coated stainless steel bushing. For more information refer to page 81
POHI		Wheel: High-quality, impact and heat-resistant nylon Bickie TempLine® Performance, 85° shore D, gray. Bearing type: Plain bore with teflon-coated stainless steel bushing. For more information refer to page 82

Bickie
TempLine® Comfort

Bickie
TempLine® Performance

Swivel casters	Rigid casters	Swivel casters with 'stop-fix' brake	Wheel Ø [inch] [mm]	Wheel width [inch] [mm]	Load capacity [lbs] [kg]	Bearing type	Total height [inch] [mm]	Plate size [mm]	Bolt hole spacing [mm]	For mounting bolt [inch]	Offset [inch]	G15 page
LIX-POSI series												
LIX-POSI 100G-OF-XAT	BX-POSI 100G-XAT	LIX-POSI 100G-FI-OF-XAT	4	1 1/8 [40]	220 [100]	Plain bore	4 15/16 [125]	100 x 85	80 x 60	5/16	1 1/16	384
LIX-POSI 125G-OF-XAT	BX-POSI 125G-XAT	LIX-POSI 125G-FI-OF-XAT	5	1 1/8 [40]	265 [120]	Plain bore	5 7/8 [150]	100 x 85	80 x 60	5/16	1 1/16	384
LIX-POHI series												
LIX-POHI 100G-OF-XAT	BX-POHI 100G-XAT	LIX-POHI 100G-FI-OF-XAT	4	1 1/8 [30]	330 [150]	Plain bore	4 15/16 [125]	100 x 85	80 x 60	5/16	1 1/16	392
LIX-POHI 125G-OF-XAT	BX-POHI 125G-XAT	LIX-POHI 125G-FI-OF-XAT	5	1 1/8 [40]	330 [150]	Plain bore	5 7/8 [150]	100 x 85	80 x 60	5/16	1 1/16	392

All casters on this page are suitable for autoclaves and washdown applications.

Image of teflon-coated stainless steel bushing (XAT)



More options in the Bickie general catalog G15!

Options



	With high temperature stainless steel ball bearings in the wheel	With heat-resistant grease in the swivel head	With silicone rubber tread and aluminum wheel center	LIX-POHI series wheel Ø 3 1/8", 6", 8" *	For mounting bolt Ø 1/2"	Stainless steel heat-resistant medium duty casters	Natural color, temperature range -20° F to +340° F **
Product code suffix	-HXX	remove suffix -OF	LIX-ALSI series		LIXR series	LIXX series	LIX-POH series
Available for	POHI series upon request	upon request	wheel Ø 4" upon request	upon request	wheel Ø 3 1/8"-5" upon request	upon request	upon request

* Wheel Ø 6" and 8" with plate size 140 x 110 mm and bolt hole spacing 105 x 75-80 mm

** Operating temperature temporarily up to +430° F