

## POTH Series

Wheels with Polyurethane Tread,  
with Heavy Nylon Wheel Center

660 - 1,750 lbs

✓RoHS



<b>Tread &amp; tire hardness</b>	94° shore A
<b>Temperature resistance</b>	-15° F - +160° F temporarily up to +195° F
<b>Rolling resistance</b>	very good
<b>Operating noise</b>	good
<b>Floor surface preservation</b>	good

### POTH-wheel series:

**Tread:** Made of high-quality thermoplastic polyurethane (TPU), 94° shore A hardness, high operational comfort, low-noise operation, low rolling and swivel resistance, good floor preservation, high abrasion resistance, color dark gray, non-marking, non-staining, chemically bonded for an inseparable connection with the wheel center.

**Wheel center:** Made of high-quality, impact-resistant nylon, color natural white.

### Bearing types:

- Ball bearing: Two pressed-in ball bearings, lubricated with long-life grease.
- Ball bearing (C): A centrally encapsulated sealed ball bearing within the injected nylon, lubricated with long-life grease.

### Other features:

Very high chemical resistance to many aggressive substances.

Operating temperature: -15° F to +160° F, temporarily up to +195° F.

At ambient temperatures above +95° F the load capacity is reduced.

Maintenance-free under standard conditions.

Wheels	Wheel Ø (D)		Wheel width (T2)		Load capacity		Bearing type	Axle bore Ø (d) [mm]	Hub length (T1)		G15 page
	[inch]	[mm]	[inch]	[mm]	[lbs]	[kg]			[inch]	[mm]	
POTH series											
POTH 100/10K	4	[100]	1 ¾	[35]	660	[300]	Ball bearing (C)	10	1 25/32	[46]	213
POTH 125/10K	5	[125]	1 9/16	[40]	770	[350]	Ball bearing (C)	10	1 25/32	[46]	213
POTH 150/20K	6	[150]	1 ¾	[45]	1100	[500]	Ball bearing	20	2 11/32	[60]	213
POTH 200/20K	8	[200]	2	[50]	1750	[800]	Ball bearing	20	2 11/32	[60]	213
POTH series - stainless steel											
POTH 150/20XK	6	[150]	1 ¾	[45]	1100	[500]	Ball bearing	20	2 11/32	[60]	213
POTH 200/20XK	8	[200]	2	[50]	1750	[800]	Ball bearing	20	2 11/32	[60]	213



**BUSHING**  
REFER TO PAGE 20

# CasterDepot

More  
options in the  
Blickle general  
catalog  
G15!

Options



Wheel with additional  
ball bearing seals

Product code suffix

-KD

Available for

upon request

