






## VE Series

Wheels with Standard Solid Rubber Tires,  
with Pressed Steel Rim

 110 - 450 lbs

 RoHS



<b>Tread &amp; tire hardness</b>		80° shore A
<b>Temperature resistance</b>		-15° F - +175° F
<b>Rolling resistance</b>		reasonable
<b>Operating noise</b>		very good
<b>Floor surface preservation</b>		very good

### VE-wheel series:

**Tires:** Made of standard solid rubber, 80° shore A hardness, very high operational comfort, low-noise operation, very good floor preservation, color black, PAH conform in accordance to EU-directive 2005/69/EC.

**Rims:** Made of pressed steel, zinc-plated, blue-passivated, Cr6-free.

### Bearing type:

- Roller bearing, lubricated with long-life grease

### Other features:

Chemical resistance to many aggressive substances, except oils.

Operating temperature: -15° F to +175° F.

At ambient temperatures above +140° F the load capacity is reduced.

Maintenance-free under standard conditions.

Wheels	Wheel Ø		Tire width (T2)		Load capacity		Bearing type	Axle bore Ø (d) [mm]	Hub length (T1)		G15 page
	[inch]	[mm]	[inch]	[mm]	[lbs]	[kg]			[inch]	[mm]	
VE 80/12R	3 1/8	[80]	1	[25]	110	[50]	Roller bearing	12	1 3/8	[35]	132
VE 100/12R	4	[100]	1 1/8	[30]	155	[70]	Roller bearing	12	1 3/4	[45]	132
VE 125/12R	5	[125]	1 1/2	[37.5]	220	[100]	Roller bearing	12	1 3/4	[45]	132
VE 150/20R	6	[150]	1 9/16	[40]	295	[135]	Roller bearing	20	2 1/32	[60]	132
VE 200/20R	8	[200]	2	[50]	450	[205]	Roller bearing	20	2 1/32	[60]	132

More options in the Blicke general catalog G15!

### Options



With non-marking gray tire

Electrically conductive version, black tire

Product code suffix

-SG

-EL

Available for

upon request

upon request

