

30

SERIES MEDIUM DUTY

900 LBS maximum capacity

casterdepot.com



Item Shown: 30-06201-RI-1C

FEATURES

Swivel Section: Cold forged out of 1/4" steel, the swivel section includes high-strength double row ball bearings in smooth raceways.

Legs: 1/4" steel formed for strength.

Kingpin: 5/8" diameter kingpin.

Axle: 1/2" diameter.

Lubrication: Pre-lubricated before shipping.

Wheels: 4" to 8" diameter wheels are available with straight roller bearings or ball bearings for ease in rolling.

Finish: Zinc plated for corrosion resistance.

BENEFITS

The 30 Series is constructed of cold forged steel and is recommended for medium duty applications.

APPLICATIONS

Excellent for dollies, waste disposal trucks, warehouse trucks, proof or cooling racks, portable work benches, floor trucks, shop carts, drywall dollies, trailer frames, wire shelving units, tool boxes, laundry distribution carts, manual lifting devices, unitized dairy distribution carts and other medium duty applications.

OPTIONS

Brakes:

Cam: C*




Swivel Locks:

Factory Installed: L

Demountable: DL


Sealed Wheels: SW

*For wheels with diameter >6

		
Top Plate Size	Bolt Hole Spacing	Bolt Diameter
Std: 4.0 x 4.5	2.625 x 3.625 Slotted to 3.0 x 3.0	0.375
OT 35: 5.0 x 5.5	4.12 x 4.50	0.375

CasterDepot

30 Series Cross Sectional View



WHEEL			CAPACITY			PART NUMBER		
Dia.	Width	Material	Roller Bearing	OAH	Swivel Lead	Straight Roller	Precision Ball	Wt.
4	1.50	Forged Steel	900	5.63	1.38	30-04101-20-1		6.00
4	2.00	Phenolic Resin	700	5.63	1.38	30-04201-30-1		6.50
4	2.00	Standard Polyurethane	750	5.63	1.38	30-04201-60-1		7.50
4	2.00	H.D. T/R Polyurethane	600	5.63	1.38	30-04201-66-1	30-04202-66-1	7.50
5	2.00	Forged Steel	900	6.50	1.69	30-05201-20-1		8.00
5	2.00	Phenolic Resin	900	6.50	1.69	30-05201-30-1		7.00
5	2.00	Standard Polyurethane	900	6.50	1.69	30-05201-60-1		9.00
5	2.00	T/R Polyurethane	800	6.50	1.69	30-05201-61-1	30-05202-61-1	8.00
6	2.00	Forged Steel	900	7.50	2.00	30-06201-20-1		10.00
6	2.00	Phenolic Resin	900	7.50	2.00	30-06201-30-1		8.00
6	2.00	Standard Polyurethane	900	7.50	2.00	30-06201-60-1	30-06202-60-1	10.00
6	2.00	T/R Polyurethane	900	7.50	2.00	30-06201-61-1	30-06202-61-1	9.00
8	2.00	Phenolic Resin	900	9.50	2.38	30-08201-30-1		9.00
8	2.00	Polyurethane	900	9.50	2.38	30-08201-60-1	30-08202-60-1	10.00
8	2.00	Soft Polyurethane	900	9.50	2.38	30-08201-61-1	30-08202-61-1	9.00

Capacity listed is for manual operation. For powered operations, consult factory.
 Part numbers listed are for the swivel caster. For rigid casters, change the last digit from 1 to 2 (i.e. 30-06201-30-2)
 Estimated weight is for the swivel caster. Deduct 20% of swivel caster weight for rigid caster.
 * These casters have annular ball bearings.
 All dimensions are in inches. All weights are in pounds.

