





[casterdepot.com](http://casterdepot.com)

## O Stainless Steel



### WHEELS

	Diameter x tread (mm)	Hub x bore (mm)	Max load (kg)
 <b>HBS*</b> Blue high resilience elastomer, stainless steel roller bearing, no thread guard	150 x 40	60 x 12.7	230
	200 x 50	60 x 12.7	250
 <b>HSS*</b> Grey high resilience elastomer, stainless steel roller bearing, optional thread guard	200 x 50	60 x 12.7	250
 <b>HUS*</b> Polyurethane on nylon, stainless steel roller bearing, no thread guard	100 x 40	60 x 12.7	300
	125 x 40	60 x 12.7	350
	150 x 40	60 x 12.7	450
 <b>ONS...WS*</b> Hard nylon, stainless steel roller bearing, no thread guard	200 x 48	60 x 12.7	450
	100 x 40	60 x 12.7	350
	125 x 40	60 x 12.7	380
	150 x 40	60 x 12.7	450
	200 x 40	60 x 12.7	500

### FORKS<sup>1</sup>

**OSP**  
Plate with swivel**HSF**  
Fixed plate, no swivel**OSPTB**  
Plate with swivel and total brake**OSPDL**  
Plate with swivel and direction lock

### ORDER CODES

Wheel code	Fork code	Castor code
<b>HBS150</b> Diameter: <b>150 mm</b>	O150SP H150SF O150SPTB O150SPDL	HBS150/OSP HBS150/HSF HBS150/OSPTB HBS150/OSPDL
<b>HBS200</b> Diameter: <b>200 mm</b>	O200SP H200SF O200SPDL	HBS200/OSP HBS200/HSF HBS200/OSPDL
<b>HSS200<sup>2</sup></b> Diameter: <b>200 mm</b>	O200ZP O200ZF O200ZPDL	HSS200/OSP HSS200/HSF HSS200/OSPDL
<b>HUS100</b> Diameter: <b>100 mm</b>	O100SP H100SF O100SPTB O100SPDL	HUS100/OSP HUS100/HSF HUS100/OSPTB HUS100/OSPDL
<b>HUS125</b> Diameter: <b>125 mm</b>	O125SP H125SF O125SPTB O125SPDL	HUS125/OSP HUS125/HSF HUS125/OSPTB HUS125/OSPDL
<b>HUS150</b> Diameter: <b>150 mm</b>	O150SP H150SF O150SPTB O150SPDL	HUS150/OSP HUS150/HSF HUS150/OSPTB HUS150/OSPDL

Wheel code	Fork code	Castor code
<b>HUS200</b> Diameter: <b>200 mm</b>	O200SP H200SF O200SPTB O200SPDL	HUS200/OSP HUS200/HSF HUS200/OSPTB HUS200/OSPDL
<b>ONS100W</b> Diameter: <b>100 mm</b>	O100SP H100SF O100SPTB O100SPDL	ONS100W/OSP ONS100W/HSF ONS100W/OSPTB ONS100W/OSPDL
<b>ONS125W</b> Diameter: <b>125 mm</b>	O125SP H125SF O125SPTB O125SPDL	ONS125W/OSP ONS125W/HSF ONS125W/OSPTB ONS125W/OSPDL
<b>ONS150W</b> Diameter: <b>150 mm</b>	O150SP H150SF O150SPTB O150SPDL	ONS150W/OSP ONS150W/HSF ONS150W/OSPTB ONS150W/OSPDL
<b>ONS200W</b> Diameter: <b>200 mm</b>	O200SP H200SF O200SPTB O200SPDL	ONS200W/OSP ONS200W/HSF ONS200W/OSPTB ONS200W/OSPDL

<sup>2</sup> For optional thread guards, add **G** at the end of wheel code.

\* Wheels also available with plain bearing—HBA, HSA, HUA...S, ONA...WS.

<sup>1</sup> See page 18 for O Series fork dimensions.

Also available with North American plate.