










[casterdepot.com](http://casterdepot.com)

## Polyurethane wheels






	Diameter x tread (mm)
 <b>AUQ</b> Polyurethane on cast iron, precision bearing, no thread guard	200 x 102 250 x 102
 <b>HUR</b> Polyurethane on nylon, roller bearing, optional thread guard (150 mm wheel only)	100 x 40 125 x 40 150 x 40
 <b>HUS*</b> Polyurethane on nylon, stainless steel roller bearing, no thread guard	100 x 32 125 x 40 150 x 40 200 x 48
 <b>JUR*</b> Polyurethane, roller bearing, optional thread guard	100 x 32 125 x 38
 <b>KUQ*</b> Polyurethane, precision bearing, optional thread guard	75 x 23 100 x 23
 <b>QUQ<sup>1</sup></b> Polyurethane tyre on nylon, precision bearing, thread guard	75 x 32 100 x 32 125 x 32
 <b>VUQ</b> Polyurethane on cast iron, precision bearing, no thread guard	203 x 75 254 x 75
 <b>WUQ</b> Polyurethane, precision bearing, no thread guard	150 x 40 200 x 40
 <b>XUQ</b> Polyurethane on cast iron, precision bearing, no thread guard	102 x 50 127 x 50 152 x 50 203 x 50

\* Also available with plain bearing—HUA, JUA, KUA.





<sup>1</sup> Also available with plain bearing (QUA) and stainless steel bearing (QUC).

## Soft wheels


### GREY RUBBER

	Diameter x tread (mm)
 <b>HSR</b> Grey rubber, energy absorbent, roller bearing, thread guard available (add <b>G</b> to the end of code)	200 x 50
 <b>KSA</b> Grey rubber, flat profile, plain bearing	65 x 23 75 x 23 100 x 23
 <b>PSA</b> Grey rubber, non-marking, white polypropylene offset wheel, plain bearing. Developed for floor polishers and scrubbers. Also available to suit 5/8" bore (58)	200 x 32
 <b>PSB</b> Grey rubber, non-marking, white polypropylene offset wheel, deep groove ball bearing. Developed for floor polishers and scrubbers	200 x 32
 <b>STQ</b> Grey energy absorbent elastomer, round profile, precision bearing, thread guard	75 x 32 100 x 32 125 x 32




### BLUE RUBBER

	Diameter x tread (mm)
 <b>CBQ</b> Blue high resilience elastomer, precision bearing, thread guard	75 x 33 100 x 33 125 x 33
 <b>HBR</b> Blue high-resilient rubber, non-marking, long life, roller bearing	150 x 40 200 x 50
 <b>JBR</b> Blue high-resilient rubber, non-marking, long life, roller bearing	100 x 32 125 x 32
 <b>MBQ</b> Blue high-resilient rubber, non-marking, long life, precision ball bearing	100 x 32 125 x 32




### BLUE RUBBER

	Diameter x tread (mm)
 <b>OBQ</b> Blue high-resilient rubber, non-marking, long life, precision ball bearing	100 x 50 125 x 50 150 x 50 200 x 50





### BLACK RUBBER—SMALL

	Diameter x tread (mm)
 <b>PRB*</b> General purpose rubber utility wheel for lawn equipment and carts, deep groove ball bearing	125 x 36 150 x 36 200 x 36
 <b>RB200L</b> Solid black rubber wheel, with roller bearing, for wheelbarrows, utility equipment and waste bins	200 x 50
 <b>U200/60C</b> Medium duty hand truck wheels, deep groove ball bearing, high-impact polypropylene centre, 20 mm bore (-POYB20) or 3/4" bore (-POYB34)	200 x 60

### BLACK RUBBER—LARGE

	Diameter x tread (mm)
 <b>PRP250</b> General purpose rubber utility wheel, used on light lawn equipment and carts, plain bearing. Optional hubcap available (GHUBCAP)	250 x 45
 <b>R250/50C<sup>1</sup></b> Puncture proof for wheelbarrows and utility equipment, precision ball bearing. Available in 20 mm bore (-PRYQ20) or 3/4" bore (-PRYQ34)	250 x 50
 <b>R300/50C<sup>1</sup></b> Puncture proof for wheelbarrows and utility equipment, precision ball bearing. Available in 20 mm bore (-PRYQ20) or 3/4" bore (-PRYQ34)	300 x 50

## BLACK RUBBER – LARGE

	Diameter x tread (mm)
 <b>R400/70C<sup>1</sup></b> Puncture proof for wheelbarrows and utility equipment, precision ball bearing. Available in 20 mm bore (-PRYQ20), 3/4" bore (-PRYQ34), or 1" bore (PRYQ25)	<b>400 x 70</b>
 <b>R250/75C<sup>2</sup></b> Puncture proof for wheelbarrows and utility equipment, precision ball bearing. Available in 20 mm bore (-PRWQ20), 25 mm bore (-PRWQ25), 3/4" bore (-PRWQ34), or 5/8" bore (-PRWQ58)	<b>250 x 75</b>
 <b>R280/70R</b> Puncture proof solid cushioned wheel, with deep groove ball bearings in sizes 1" (-SRBB10), 20 mm (-SRBB20), 3/4" (-SRBB34), or 5/8" (-SRBB58)	<b>280 x 70</b>
 <b>R400X8-SQ10</b> Heavy duty wheel, designed for towing, precision ball bearing. Max tow speed—15 km/h	<b>400 x 95</b>

## ORDER CODES

	Max load (kg)	Hub x bore (mm)
Polyurethane		
AUQ200	3000	<b>109 x 30</b>
AUQ250	3500	<b>109 x 30</b>
HUR100	300	<b>60 x 12.7</b>
HUR125	350	<b>60 x 12.7</b>
HUR150	450	<b>60 x 12.7</b>
HUR200	500	<b>60 x 12.7</b>
HUS100	300	<b>60 x 12.7</b>
HUS125	350	<b>60 x 12.7</b>
HUS150	450	<b>60 x 12.7</b>
HUS200	500	<b>60 x 12.7</b>
JUR100	300	<b>45 x 10</b>
JUR125	300	<b>45 x 10</b>

## ORDER CODES

	Max load (kg)	Hub x bore (mm)
KUQ75	100	<b>30 x 8</b>
KUQ100	100	<b>30 x 8</b>
QUQ75	200	<b>40 x 8</b>
QUQ100	200	<b>40 x 8</b>
QUQ125	200	<b>40 x 8</b>
VUQ200	2000	<b>89 x 20</b>
VUQ250	2000	<b>89 x 20</b>
WUQ150	600	<b>60 x 12.7</b>
WUQ200	600	<b>60 x 12.7</b>
XUQ100	600	<b>62 x 12.7</b>
XUQ125	800	<b>62 x 12.7</b>
XUQ150	1000	<b>62 x 12.7</b>
XUQ200	1000	<b>62 x 12.7</b>
Grey Rubber		
HSR200	250	<b>60 x 12.7</b>
KSA65	50	<b>30 X 12</b>
KSA75	50	<b>30 X 12</b>
KSA100	50	<b>30 X 12</b>
PSA200	80	<b>38 x 12.7</b>
PSA200(58)	80	<b>38 x 16</b>
PSB200	80	<b>38 x 12.7</b>
STQ75	100	<b>40 x 8</b>
STQ100	100	<b>40 x 8</b>
STQ125	100	<b>40 x 8</b>
200X50RIB-PR20	75	<b>60 x 20</b>
200X50RIB-PQ12	75	<b>60 x 12</b>
P200X50RIB-SQ05	50	<b>60 x 12.7</b>
Blue Rubber		
CBQ75	85	<b>40 x 8</b>
CBQ100	100	<b>40 x 8</b>
CBQ125	100	<b>40 x 8</b>

## ORDER CODES

	Max load (kg)	Hub x bore (mm)
HBR150	230	<b>60 x 12.7</b>
HBR200	250	<b>60 x 12.7</b>
JBR100	150	<b>45 x 10</b>
JBR125	180	<b>45 x 10</b>
MBQ100G	140	<b>40 x 8</b>
MBQ125G	150	<b>40 x 8</b>
OBQ100	300	<b>60 x 12.7</b>
OBQ125	350	<b>60 x 12.7</b>
OBQ150	400	<b>60 x 12.7</b>
OBQ200	400	<b>60 x 12.7</b>
Black Rubber—Small		
PRB125	50	<b>38 x 13</b>
PRB150	75	<b>38 x 13</b>
PRB200	100	<b>38 x 13</b>
RB200L	200	<b>60 x 25.4</b>
U200/60C-POYB20	135	<b>60 x 20</b>
U200/60C-POYB34	135	<b>60 x 19</b>
Black Rubber—Large		
PRP250	100	<b>48 x 16</b>
R250/50C-PRYQ20	150	<b>60 x 20</b>
R300/50C-PRYQ20	150	<b>60 x 20</b>
R400/70C-PRYQ20	150	<b>80 x 20</b>
R250/75C-PRWQ20	180	<b>75 x 20</b>
R280/70R-SRBB10	200	<b>60 x 25</b>
R400X8-SQ10	600	<b>80 x 25</b>

\* Also available with plain bearing—PRA.

<sup>1</sup> 5/8" and 3/4" precision ball bearing or plain bush available.

<sup>2</sup> 20 mm, 5.8", 3/4" deep groove ball bearing, or 5/8", 3/4" plain bush available.