








V Series 2450 KG

WHEELS

	Diameter x tread (mm)	Hub x bore (mm)	Max load (kg)
 VUQ Polyurethane on cast iron, precision bearing, no thread guard	203 x 75	89 x 20	2000
	254 x 75	89 x 20	2000
 VXQ High impact polymer, precision bearing, no thread guard	200 x 75	89 x 20	2450
	250 x 75	89 x 20	2450



FORKS

	Wheel Diameter	Height (mm)	Turning radius (mm)
 VZP Plate with swivel	200	267	165
	250	318	190
 VZF Fixed plate, no swivel	200	267	-
	250	318	-
 VZPBR Plate with swivel and wheel brake	200	267	317
	250	318	353
 VZPDL Plate with swivel and direction lock	200	267	165
	250	318	190





ORDER CODES

Wheel code	Fork code	Castor code
VUQ200 Diameter: 203 mm	V200ZP	VUQ200/VZP
	V200ZF	VUQ200/VZF
	V200ZPBR	VUQ200/VZPBR
VUQ250 Diameter: 254 mm	V250ZP	VUQ250/VZP
	V250ZF	VUQ250/VZF
	V250ZPBR	VUQ250/VZPBR
VXQ200 Diameter: 203 mm	V200ZPDL	VUQ250/VZPDL
	V250ZPDL	VUQ250/VZPDL
	V250ZPDL	VUQ250/VZPDL
VXQ250 Diameter: 254 mm	V250ZP	VXQ250/VZP
	V250ZF	VXQ250/VZF
	V250ZPBR	VXQ250/VZPBR
	V250ZPDL	VXQ250/VZPDL
	V250ZPDL	VXQ250/VZPDL
	V250ZPDL	VXQ250/VZPDL





A Series 3500 KG

WHEELS

	Diameter x tread (mm)	Hub x bore (mm)	Max load (kg)
 AUQ Polyurethane on cast iron, precision bearing, no thread guard	200 x 102	109 x 30	3000
	250 x 102	109 x 30	3500



FORKS

	Wheel Diameter	Height (mm)	Turning radius (mm)
 AZP Plate with swivel	200	279	172
	250	330	197
 AZF Fixed plate, no swivel	200	279	-
	250	330	-
 AZPBR Plate with swivel and wheel brake	200	279	317
	250	330	353
 AZPDL Plate with swivel and direction lock	200	279	172
	250	330	197

ORDER CODES

Wheel code	Castor code
AUQ200 Diameter: 200 mm	AUQ200/AZP
	AUQ200/AZF
	AUQ200/AZPBR
	AUQ200/AZPDL
AUQ250 Diameter: 250 mm	AUQ250/AZP
	AUQ250/AZF
	AUQ250/AZPBR
	AUQ250/AZPDL