

GDSD series

Shock absorbing casters - Fine shock absorbing



kg 100 ~ 350 kg

✓ RoHS

- Equipment or carts in cleanroom
- Medical equipment
- Equipment or carts in need of shock absorbing
- Auto ware house
- Trolleys for hotel or restaurant



Swivel

GDSD-100-ASF



Rigid

GDSD-100-ARF


Swivel/Brake

WHEELR
TYPES ber

LUD 65'

HUD 65'

✓ Recommended Load = Load Cap. X 3 ✓ Temp. Range : -10 ~ 90°C



[mm]	[mm]	[kg]	[mm]	[mm]	[mm]	[mm]	[mm]
100	30x2	100	162.5-20	45~53	73x73	58x58	7
130	40x2	350	227-30	50~66	95x95	70x70	11



Swivel

GDSD-100-ASS



Rigid

GDSD-100-ARS

Swivel/Brake

WHEELR
TYPES ber

LUD 65'

✓ Recommended Load = Load Cap. X 3 ✓ Temp. Range : -10 ~ 90°C



[mm]	[mm]	[kg]	[mm]	[mm]	[mm]	[mm]
100	30x2	100	162.5-20	45~53	M12x1.75P	18

CasterDepot®

✓ Wheel types


LUD

HUD

- Cast PU(Shore A 90)
- Aluminum core
- 2 Ball bearings

- Cast PU(Shore A 95)
- Aluminum core
- 2 Ball bearings

✓ Materials



- ① Top plate : Pressed steel(100), Forged steel(130)
- ② Frame : Aluminum
- ③ Leg : Pressed steel
- ④ Spring : Special rubber
- ⑤ Wheel : Refer to wheel types
- ⑥ Finish : Powder coating & Zinc galvanized

✓ Options

- WEU : Anti-static Polyurethane(Black Color), Top plate Zinc galvanized