

GDSP series

Shock absorbing casters -
Towable by a power car within 20km/h

kg 360 ~ 450 kg

✓ RoHS



- Carts for automobile parts
- Trolleys in cleanroom
- Equipment or carts in need of shock absorbing
- Auto ware house
- Equipment or carts towed by a car




✓ Recommended Load = Load Cap. X 3 ✓ Temp. Range : -10 ~ 90°C

	Swivel	Rigid	Swivel/Brake	Rigid/Brake	WHEEL TYPES	Rubber [mm]	Roller [mm]	Load [kg]	Swivel [mm]	Rigid [mm]	Swivel/Brake [mm]	Rigid/Brake [mm]	
GDSP-150-ASF	GDSP-150-ARF	GDSP-150-BSF	GDSP-150-BRF	MUD	65'	150	48	360	202-14	48-53	158x114	133x86 125x62	13
GDSP-200-ASF	GDSP-200-ARF	GDSP-200-BSF	GDSP-200-BRF	MUD	75'	200	48	450	253-15	65-75	158x114	133x86 125x62	13



✓ Plate type



✓ Wheel types


MUD(Blue)



MUD(Beige)

- Cast PU(Shore A 95)
- Aluminum core
- 2 Ball bearings
- Cast PU(Shore A 95)
- Aluminum core
- 2 Ball bearings

✓ Materials



- ① Top plate : Pressed steel
- ② Frame : Pressed steel
- ③ Leg : Pressed steel
- ④ Spring : Special rubber
- ⑤ Wheel : Refer to wheel types
- ⑥ Finish : Zinc galvanized

✓ Options

- DL : Directional lock is available(One touch system).