

GSST series

Shock absorbing casters -
Towable by a power car within 20km/h

kg 400 ~ 1,350 kg









✓ RoHS



- Carts for automobile parts
- Trolleys in cleanroom
- Equipment or carts in need of shock absorbing
- Auto ware house
- Equipment or carts towed by a car



✓ Recommended Load = Load Cap. X 3 ✓ Temp. Range : -10 ~ 90°C

Swivel	Rigid	Swivel/Brake	WHEELRub TYPES ber	 [mm]	 [mm]	 [kg]	 [mm]	 [mm]	 [mm]	 [mm]	 [mm]
GSST-130-ASF	GSST-130-ARF	GSST-130-BSF	HUD 65° 75°	130	40	400	200-21	46-55	160x120	135x85 125x65	15
GSST-150-ASF	GSST-150-ARF	GSST-150-BSF	HUD 65° 75°	150	40	400	232-30	46-61	160x120	135x85 125x65	15
GSST-200-ASF	GSST-200-ARF	GSST-200-BSF	HUD 65° 75°	200	40	400	276-30	50-70	160x120	135x85 125x65	15
GSST-200W-ASF	GSST-200W-ARF		HUD 75°	200	48	500	279-30	50-68	160x135	140x105 105x80	14
GSST-250-ASF	GSST-250-ARF	-	HUD 65° 75°	250	60	1,350	362-30	78-92	175x140	148x111 132x99	14




✓ Wheel types

HUD

- Cast PU(Shore A 95)
- Aluminum core
- 2 Ball bearings

✓ Materials



- ① Top plate : Forged steel
- ② Frame : Pressed steel
- ③ Leg : Pressed steel
- ④ Spring : Special rubber
- Wheel : Refer to wheel types
- ⑥ Finish : Powder coating & Zinc galvanized

✓ Options