

Injection PU/Rubber Wheels

Light Duty Wheels

kg 40 ~ 210 kg

✓ RoHS



Light duty Injection PU/High grade Rubber Wheels

- ✓ Elegant appearance
- ✓ Strong impact resistance by the application of PP core
- ✓ Strong oil resistance, Strong corrosion resistance
- ✓ Non marking
- ✓ Temp. Range : -10 ~ +90°C

Model	Wheel types	Details	Wheel dia (D)	Wheel width (W)	Shaft dia. (A)	Hub length (L)	Load capacity (kg)	Bearing
TUN	TUN-50-24	✓ Injection PU(Shore D92) ✓ No bearing	50	24	6	29	40	X
	TUN-64-24		64	24	6	29	50	X
	TUN-75-25		75	25	8	40	75	X
	TUN-100-30		100	30	8	40	100	X
	TUN-125-30		125	30	8	40	110	X
TUS	TUS-75-25	✓ Injection PU(Shore D92) ✓ 1 Ball bearing	75	25	8	40	75	6202 ZZ
	TUS-100-30		100	30	8	40	100	6202 ZZ
	TUS-125-30		125	30	8	40	110	6202 ZZ
TUD	TUD-100-30	✓ Injection PU(Shore D92) ✓ 2 Ball bearings	100	30	8	30	100	608 ZZ
	TUD-125-30		125	30	8	30	110	608 ZZ
	TUD-130-48		130	48	15	50	180	6202 ZZ
	TUD-150-30		150	30	8	30	110	608 ZZ
	TUD-150-48		150	48	15	50	210	6202 ZZ
HRN	HRN-50-24	✓ Rubber(Shore D85) ✓ No bearing	50	24	6	29	40	X
	HRN-64-24		64	24	6	29	50	X
	HRN-75-25		75	25	8	40	75	X
	HRN-100-30		100	30	8	40	100	X
	HRN-125-30		125	30	8	40	110	X
HRS	HRS-75-25	✓ Rubber(Shore D85) ✓ 1 Ball bearing	75	25	8	40	75	6202 ZZ
	HRS-100-30		100	30	8	40	100	6202 ZZ
	HRS-125-30		125	30	8	40	110	6202 ZZ
HRD	HRD-100-30	✓ Rubber(Shore D85) ✓ 2 Ball bearings	100	30	8	30	100	608 ZZ
	HRD-125-30		125	30	8	30	110	608 ZZ
	HRD-130-48		130	48	15	50	180	6202 ZZ
	HRD-150-30		150	30	8	30	110	608 ZZ
	HRD-150-48		150	48	15	50	210	6202 ZZ

Wheel types **

