

Light Duty/Soft Polyurethane wheels

Light Duty/Soft Polyurethane Wheels

AL CORE

kg 90 ~ 330 kg

✓ RoHS



High quality polyurethane wheels

- ✓ Light weight. Strong corrosion resistance by the application of the aluminum core
- ✓ High quality polyurethane + Excellent adhesion
- ✓ Strong oil resistance, Strong corrosion resistance
- ✓ Satisfy the elasticity and durability at a time
- ✓ Anti-static wheel is available(Black color, non-marking) ⚡
- ✓ Temp. range : -10 ~ +90°C


Model	Wheel types	Details	Wheel dia (D)	Wheel width (W)	Shaft dia. (A)	Hub length (L)	Load capacity (kg)	Bearing
LUD	LUD-75-30		75	30	8	30	90	608 ZZ
	LUD-100-30	✓ Cast PU(Shore A90)	100	30	8	30	120	608 ZZ
	LUD-125-30	✓ Aluminum core	125	30	8	30	120	608 ZZ
	LUD-150-30	✓ 2 Ball bearings	150	30	8	30	120	608 ZZ
LUD-WEU	LUD-WEU-75-30	✓ Cast PU(Shore A90)	75	30	8	30	90	608 ZZ
	LUD-WEU-100-30	✓ Aluminum core	100	30	8	30	120	608 ZZ
	LUD-WEU-125-30	✓ 2 Ball bearings	125	30	8	30	120	608 ZZ
	LUD-WEU-150-30	✓ Anti-static version (10 ⁶ - 10 ⁷ Ωcm)	150	30	8	30	120	608 ZZ
SUD(75°)	SUD(75°)-100-40	✓ Cast PU(Shore A75)	100	40	15	50	200	6202 ZZ
	SUD(75°)-130-40	✓ Aluminum core	130	40	15	50	270	6202 ZZ
	SUD(75°)-150-40	✓ 2 Ball bearings	150	40	15	50	330	6202 ZZ
SUNS / SUND	SUNS-75-25	✓ Cast PU(Shore A75)	75	25	8	40	90	6202 ZZ
	SUND-100-30	✓ Nylon core	100	30	8	30	100	608 ZZ
	SUND-125-30	✓ 2 Ball bearings(SUNS 1 Bearing)	125	30	8	30	110	608 ZZ

CasterDepot®

Wheel types **



LUD/SUND



SUD

