

# PH series

## Medium duty casters

kg 200 ~ 600 kg








✓ RoHS



- Carts for material handling purpose in factories
- Moving for heavy size equipment
- Medium duty purpose carts



✓ Recommended Load = Load Cap. X 3    ✓ Temp. Range : -10 ~ 90°C

	Swivel	Rigid	Swivel/Brake	WHEEL TYPES	 [mm]	 [mm]	 [kg]	 [mm]	 [mm]	 [mm]	 [mm]	
PH-100-ASF		PH-100-ARF	PH-100-BSF	HUD	100		48	157	50	100x85	80x60 77x45	9
				MUD			40					
				SUD			40					
				MCD			48					
				NYD			48					
PH-130-ASF		PH-130-ARF	PH-130-BSF	HUD	130		40	186	50	100x85	80x60 77x45	9
				MUD			40					
				SUD			40					
				HUWD			48					
				MCD			48					
PH-150-ASF		PH-150-ARF	PH-150-BSF	HUD	150		40	206	50	100x85	80x60 77x45	9
				MUD			40					
				SUD			40					
				HUWD			48					
				MCD			48					



### ✓ Wheel types

MUD



- Cast PU(Shore A 95)
- Aluminum core
- 2 Ball bearings

HUD

- Cast PU(Shore A 95)
- Aluminum core
- 2 Ball bearings

SUD

- Cast PU(Shore A 75)
- Aluminum core
- 2 Ball bearings

HUWD



- Cast PU(Shore A 95)
- Aluminum core
- 2 Ball bearings

MCD

- MC nylon(Shore D 80)
- 2 Ball bearings

NYD



- Nylon(Shore D70)
- 2 Ball bearings

### ✓ Materials



- ① Top plate : Pressed steel
- ② Frame : Pressed steel
- ③ Wheel : Refer to wheel types
- ④ Finish : Powder coating & Zinc galvanized

### ✓ Options

- WEU : Anti-static wheel is available.(Black), Zinc galvanized Frame



PH-130-ASF-HUD-F2N-WEU