



W25 Series

Swivel Top Plate

Capacity to 220 pounds each



5-W25-513 PLT 2
(shown in photo)

FEATURES

- ✓ **Design:** heavy gauge cold rolled steel, formed for strength.
- ✓ **Finish:** bright zinc plating to resist rust and corrosion.
- ✓ **Swivel Construction:** double ball bearing with hardened raceways.
- ✓ **Axle:** 3/8" diameter bolt with lock nut.

CASTER OPTIONS

- ✓ **Bright Nickel Plating:** to order, add "5" to body of model number. (Example: 5-W255-103)
- ✓ **PosiLoc® Brake:** all stainless steel construction. To order, add "PL" to end of model number (not available on 2-1/2" wheel models).
- ✓ **VertiLoc® Brake:** to order, add "VL" to end of model number.



MOUNTING OPTIONS

Top Plate Sizes: to order, add Plate Mounting Code to end of model number. (Example: 5-W25-103 PLT 2). Note: Rigid casters available in PLT 4 only.

Mounting Code	Top Plate Size	Bolt Hole Spacing	Mounting Bolt Size
PLT 1	2-7/16" x 2-7/16"	1-3/4" x 1-3/4"	1/4"
PLT 2	1-3/4" x 3"	1" x 2-1/4"	1/4"
PLT 4	2-3/8" x 3-5/8"	1-3/4" x 3"	5/16"

WHEEL OPTIONS



Cushion or Hard Rubber Conductive Rubber Cushion or Hard Rubber w/Side Plates Advantage TPR Round and Flat Advantage Heat Flat or Round Advantage Health Antimicrobial Welded Disc Blue Poly, Black or Grey Rubber Polyolefin Phenolic PolyLoc Grey or Blue

Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Type	Bearing	Capacity (Pounds)	Swivel Top Plate Model Number	Approximate Weight (Pounds)	Load Height (Inches)	Swivel Radius (Inches)
3	1 1/4	CUSHION RUBBER	DELIRIN	110	3-W25-105	1-3/4	4 1/8	3
		CUSHION RUBBER	BALL	110	3-W25-152	1-3/4		
		HARD RUBBER	DELIRIN	160	3-W25-106	1-3/4		
		HARD RUBBER	BALL	160	3-W25-162	1-3/4		
		POLYOLEFIN	PLAIN	180	3-W25-521	1-3/4		
1 1/2	PHENOLIC	PLAIN	220	3-W25-121	1-3/4			
	4	CUSHION RUBBER	DELIRIN	120	4-W25-105	2-3/8	5 1/8	3 1/2
CUSHION RUBBER W/ SIDE PLATES		BALL	120	4-W25-452	2-3/8			
WELDED DISC / BLACK RUBBER		BALL	150	4-W25-113	2-1/2			
WELDED DISC / GREY RUBBER		BALL	150	4-W25-113G	2-1/2			
HARD RUBBER		DELIRIN	180	4-W25-106	2-3/8			
HARD RUBBER W/ SIDE PLATES		BALL	180	4-W25-462	2-3/8			
ADVANTAGE TPR / ROUND ¹		BALL	180	4-W25-213GD	2-1/2			
WELDED DISC / POLYURETHANE		BALL	200	4-W25-113P	2-1/2			
POLYLOC / GREY ²		BALL	200	4-W25-213G	2-1/2			
POLYLOC / BLUE		BALL	200	4-W25-213P	2-1/2			
POLYOLEFIN		PLAIN	200	4-W25-513	2-1/2			
ADVANTAGE TPR / FLAT ³		BALL	220	4-W25-213GF	2-1/2			
ADVANTAGE HEAT ROUND		SS BALL	220	4-W25-213RTR	2-1/2			
ADVANTAGE HEAT FLAT		SS BALL	220	4-W25-213RTF	2-1/2			
ADVANTAGE HEALTH	SS BALL	220	4-W25-213MF	2-1/2				
1 1/2	PHENOLIC	PLAIN	220	4-W25-121	2-1/2			
5	1 1/4	CUSHION RUBBER	DELIRIN	150	5-W25-105	2-3/4	6 1/4	4
		CONDUCTIVE CUSHION RUBBER	SINTERED	150	5-W25-105C	2-3/4		
		CUSHION RUBBER	BALL	150	5-W25-152	2-3/4		
		CUSHION RUBBER W/ SIDE PLATES	BALL	150	5-W25-452	2-3/4		
		WELDED DISC / BLACK RUBBER	BALL	150	5-W25-113	3		
		WELDED DISC / GREY RUBBER	BALL	150	5-W25-113G	3		
		ADVANTAGE TPR / ROUND ¹	BALL	180	5-W25-213GD	3		
		HARD RUBBER	DELIRIN	200	5-W25-106	2-3/4		
		HARD RUBBER	BALL	200	5-W25-162	2-3/4		
		HARD RUBBER W/ SIDE PLATES	BALL	220	5-W25-462	2-3/4		
		WELDED DISC / POLYURETHANE	BALL	220	5-W25-113P	3		
		POLYLOC / GREY ²	BALL	220	5-W25-213G	3		
		POLYLOC / BLUE	BALL	220	5-W25-213P	3		
		POLYOLEFIN	PLAIN	220	5-W25-513	3		
		POLYOLEFIN	BALL	220	5-W25-514	3		
		ADVANTAGE TPR / FLAT ³	BALL	220	5-W25-213GF	3		
		ADVANTAGE HEAT ROUND	SS BALL	220	5-W25-213RTR	3		
		ADVANTAGE HEAT FLAT	SS BALL	220	5-W25-213RTF	3		
ADVANTAGE HEALTH	SS BALL	220	5-W25-213MF	3				
1 1/2	PHENOLIC	PLAIN	220	5-W25-121	3			

¹For delrin bearing change wheel code to 314GD. ²For delrin bearing change wheel code to 314G. ³For delrin bearing change wheel code to 314GF.



W25 SERIES

casterdepot.com