

# **00 Series** Low Profile

☑ RoHS

Environmentally friendly

#### **Features**

#### Industry leading selection and overall value

- · Fast deliveries for any order quantity
- Sleek, low profile design
- Up to 300 lb. capacity per caster
- Dual ball bearing raceways for smooth and dependable swivel
- Models with polyolefin log wheel are NSF approved

### **Applications**

- · Electronic Equipment
- Business Machines
- Store Fixtures
- · Laboratory Equipment
- Vending Machines
- Dolly Solutions
- Refrigeration Units

#### **Options**

Side Lock Brake:

Available on all 2" models. To order, add [B] to end of model.



Thumb Screw Brake:

Available by special order; consult factory for details.

Finishes: Zinc plating standard; optional finishes available. Consult factory.











Polished

Bright Nickel

Copper Chrome Oxide

Black Oxide

W	heel
:	Selection

Floor Protection<sup>1</sup> Non-Marking Durability **Cushioned Ride** Chemical Resistance



(Dark Grey)



Rubber (TPR)

(Grey)



(Loden Grey)



(Black)

**V**+



Polvolefin Dual Polyolefin Log (Black)


**V**+

anen aa2t	12 for	application	dataile
Dee Dade	40 101	addinganon	details


Wheel Diameter (Inches)	Tread Width (Inches)	Mounting Height (Inches)	Swivel Radius (Inches)	Tread Type	Dynamic Load (Pounds)	Base Model Number (Add fastening code)	Fastening Selection <sup>2</sup>
1-7/16"	1-11/16"	Stem: 2-1/8" Plate: 2-3/16"	1-3/4"	Polyolefin Log (Black)	150	C0014ZN-POL01(KK)	Threaded: 605, 741, 748 Grip Ring: 211, 273 Plate: 120
	(each): 2-	Stem:		Soft Rubber Dual (Dark Grey)	180	C0020ZN-SFR01(GG)	
		2-3/4"	2"	TPR Dual (Grey)	180	C0020ZN-TPR01(GG)	Threaded: 605, 741, 748
2"	13/16"	13/16" Plate: 2-13/16"	Brake:	Hard Rubber Dual (Loden Grey)	225	C0020ZN-HDR01(GG)	Grip Ring: 211, 273
	Log:		2-15/16"	Polyolefin Dual (Black)	225	C0020ZN-POS01(KK)	Plate: 120
	1-13/16"	2-13/10		Polyolefin Log (Black)	300	C0020ZN-P0L01(KK)	

<sup>2</sup>To order, include **blue** fastener code in **Base Model Number**. Example: C0020**605**ZN-SFR01(GG)


#### **Threaded Stem**



## **Grip Ring Stem**



# Top Plate



# 120 3-3/4"

### **Socket Options**

Shepherd has many solutions to help you mount your casters to your equipment quickly and easily. See pages 56-57 for more information.















New ultra low profile

1-7/16" diameter