Ball Soft Tread

Features

- Industry leading selection and overall value
- Fast deliveries for any order quantity
- Self-lubricating acetyl resin bearing
- No exposed axle
- Rubber tread; Urethane for 1-9/16" diameter models

Applications

- Store Fixtures
- Furniture
- Office Equipment
- Medical Equipment

Options

- **Brake:** 3" diameter models only.
- · Unfinished available
- Locking Pin: Available on 3" non-brake unfinished models. To order change "PSN" to "PNL" in Model Number.





Wheel Diameter (Inches)	Mounting Height (Inches)	Swivel Radius (Inches)	Finish Type	Dynamic Load (Pounds)	Base Model # (Add fastening code)	Brake Model # (Add fastening code)	Fastening Selection*
1-9/16" Cosmo	Thread/Plate: 1-13/16" Grip Ring/Grip Neck: 1-11/16"	1-1/16"	Bright Brass	40	PCM40BB		Threaded: 525 Grip Neck: 302 Plate: 1R
2-1/4" Nova	Threaded: 2-7/16" Grip Ring/Grip Neck: 2-5/16" Plate: 2-5/8"	1-9/16"	Bright Brass	75	PNA22BB		Threaded: 507, 525, 605, 637, 639, 828 Grip Neck: 302 Grip Ring: 211, 222, 223 Plate: 101, 113
			Bright Chrome	75	PNA22BC		
			Satin Chrome	75	PNA22SC		
			Windsor Antique	75	PNA22WA		
			Unfinished	75	PNA22UF		
3" Saturn	Thread: 3" Grip Ring/Grip Neck: 2-7/8" Plate: 3-3/16"	2-1/16" Brake: 2-5/16"	Bright Brass	100	PSN30BB	PSN30BB-B	Threaded: 512, 525, 526, 545, 605, 637, 639 Grip Neck: 302 Grip Ring: 211, 222, 223 Plate: 101, 113
			Bright Chrome	100	PSN30BC	PSN30BC-B	
			Satin Chrome	100	PSN30SC	PSN30SC-B	
			Windsor Antique	100	PSN30WA	PSN30WA-B	
			Unfinished	100	PSN30UF	PSN30UF-B	

*To order, include **blue** fastener code in **Base Model Number**. Example: PCM40<u>525</u>BB **Threaded Stem** — 545 —— 507 —— 526 — - 512 -**– 639** – **— 637** – - 605 UNC18 5/16" **Grip Neck Grip Ring Top Plate** - 211 ----- 223 ---- 222 -113 -101 -3/16" 9 3/16" bolt

Socket Options

5/16"

Shepherd has many solutions to help you mount your casters to your equipment quickly and easily. See pages 56-57 for more information









1-1/2"

